MAKING SAME

## **IN THE CLAIMS**

Please amend the claims as follows.

- 1. (Currently amended) An article comprising:
  - a heat spreader including a die side and a heat-sink side;
- a first channel through the heat spreader that communicates from the die side to the heat-sink side:
- a container barrier disposed on the heat spreader die side, wherein the container barrier and the heat spreader form a recess upon the die side; and
- a first channel through the container barrier, wherein the first channel is adjacent the heat spreader die side; and
  - a first plug disposed in the first channel through the container barrier.
- 2. (Canceled).
- 3. (Currently Amended) The article of claim 1, further including:
- a first channel through the heat spreader to communicate from the die side to the heat-sink side;
  - a first plug disposed in the first channel through the heat spreader;
- a second channel through the heat spreader to communicate from the die side to the heat-sink side.
- 4. (Previously Presented) The article of claim 1, wherein the first plug disposed in the first channel through the container barrier is gas-permeable and liquid-impermeable.
- 5. (Previously Presented) The article of claim 1, further including:
- a first plug disposed in the first channel through the heat spreader, wherein the first plug is gas-permeable and liquid-impermeable;

Title: LIQUID SOLDER THERMAL INTERFACE MATERIAL CONTAINED WITHIN A COLD-FORMED BARRIER AND METHODS OF MAKING SAME

a second channel through the container barrier to communicate from the die side to the heat-sink side; and

a second plug disposed in the second channel through the heat spreader, wherein the second plug is gas-permeable and liquid-impermeable.

- 6. (Original) The article of claim 1, wherein the container barrier is selected from a solder, a leaded solder, a lead-free solder, a reactive solder, an indium material, a tin material, a silver material, a tin-silver material, a tin-silver-indium material, and combinations thereof.
- 7. (Original) The article of claim 1, wherein the container barrier is selected from a metal; a polymer-solder hybrid; a polymer matrix and a metal preform; and a polymer matrix, a metal preform, and a middle heat transfer structure disposed therebetween.
  - 8. (Original) The article of claim 1, further including: a liquid heat-transfer medium disposed in the recess.
  - 9. (Original) The article of claim 1, further including: a liquid heat-transfer medium disposed in the recess, wherein the liquid heattransfer medium is selected from an organic composition, a metal, and combinations thereof.
  - 10. (Currently amended) A package comprising: a heat spreader including a die side and a heat-sink side; a first channel through the heat spreader to communicate from the die side to the heat-sink side;
    - a first plug disposed in the first channel through the heat spreader;
  - a container barrier disposed on the heat spreader die side, wherein the container barrier and the heat spreader forms a recess upon the die side;
    - a liquid heat-transfer medium disposed in the recess; and

Title: LIQUID SOLDER THERMAL INTERFACE MATERIAL CONTAINED WITHIN A COLD-FORMED BARRIER AND METHODS OF

MAKING SAME

a first channel through the container barrier, wherein the first channel is adjacent the heat spreader die side.

- 11. The package of claim 10, wherein the heat spreader is selected (Original) from a heat slug, a heat pipe, and an integrated heat spreader.
- 12. (Original) The package of claim 10, wherein the die side of the heat spreader includes a convoluted interface with the liquid heat-transfer medium.
  - 13. (Canceled).
  - 14. (Currently amended) The package of claim 10, further including: a first channel through the heat spreader to communicate from the die side to the heat-sink side;
  - a first plug disposed in the first channel through the heat spreader; a second channel through the heat spreader to communicate from the die side to the heat-sink side.
  - 15. (Previously Presented) The package of claim 10, further including: a first plug disposed in the first channel through the container barrier.
  - 16. (Previously Presented) The package of claim 10, further including: a first plug disposed in the first channel through the heat spreader; and a second channel through the container barrier.
  - 17. (Original) The package of claim 10, further including: a die in contact with the liquid heat transfer medium.
  - 18. (Original) The package of claim 10, further including: a die in contact with the liquid heat transfer medium; and

Title: LIQUID SOLDER THERMAL INTERFACE MATERIAL CONTAINED WITHIN A COLD-FORMED BARRIER AND METHODS OF

MAKING SAME

a mounting substrate coupled to the die.

19-26. (Canceled).

27. (Currently amended) A computing system comprising:

a heat spreader including a die side and a heat-sink side;

a first channel through the heat spreader that communicates from the die side to the heat-sink side;

a container barrier disposed on the heat spreader die side, wherein the container barrier and the heat spreader form a recess upon the die side;

a first channel through the container barrier, wherein the first channel is adjacent the heat spreader die side;

a die in contact with the container barrier;

a liquid heat-transfer medium disposed in the recess; and

dynamic random access memory coupled to the die.

- 28. The computing system according to claim 27, wherein the (Original) computing system is disposed in one of a computer, a wireless communicator, a hand-held device, an automobile, a locomotive, an aircraft, a watercraft, and a spacecraft.
- 29. (Original) The computing system according to claim 27, wherein the die is selected from a data storage device, a digital signal processor, a micro-controller, an application specific integrated circuit, and a microprocessor.

Claims 30-33. (Canceled)